



**Prima**  
PAVIMENTI SPECIALI

**PRIMA IDRO** ®  
DRAINING CONCRETE OUTDOOR  
CONTINOUS FLOORING



DRAINING CONCRETE, THE GREEN SOLUTION.

## Prima Idro®

ECO-SUSTAINABLE CEMENTITIOUS DRAINING SYSTEM

5

WHERE

6

PRODUCT TECHNICAL DATA

9

STRATIGRAPHIES & SOLUTIONS

10

BENEFITS

12

COLOR RANGE

14



WATER PASSES THROUGH CONCRETE.



PRIMA IDRO®

## ECO-SUSTAINABLE CEMENTITIOUS DRAINING SYSTEM

When it comes to designing or renovating the outdoor floor of a public or private space, be it a square, a pedestrian area, a public park or common areas paths within flat complexes, the most complicated aspect of the design is choosing the **most appropriate material and measures to drain rainwater**.

Essentially, right from the idea is to choose **certified materials** at the design stage that **concretely contribute** to improving outdoor spaces, avoiding as much as possible the creation of new impemeable (such as asphalt and concrete) and/or unstable (such as self-locking and loose gravel) surfaces.

Draining concrete, as the word implies, is a very porous concrete that is permeable to liquids. These floors are an ecologically sustainable solution to solve the problems related to the new development or upgrade of some urban areas, compatible with the values of respect and protection of the environment, by naturally helping the reintegration of groundwater and reducing the inflow of the same to the road surface.

All parties must be aware that during installation, concrete may have grout in the mixture.

The operating mechanism is simple: the water that arrives at the surface of Prima Idro® passes through the entire structure, reaches the subsoil and regenerates the groundwater. Part of the water is returned to the environment through evaporation, improving the thermohygrometric conditions of the site.

Prima Idro® **effectively meets the requirements of sustainability** and stability over time, allowing a drastic reduction in water collection structures, **reducing the overall cost of the project, construction and subsequent maintenance**.



## WHERE

Prima Idro® respects the environment and guarantees complete permeability. It is an environmentally sustainable solution applicable in various contexts:

- Drainage of road surfaces
- Pedestrian and bicycle paths
- Secondary and access roads
- Alleys and roads in areas of nature conservation or historical interest
- Paths near sports facilities and golf courses
- Parking areas
- Industrial and commercial yards





PERMEABLE AND DRAINING SURFACE.



## PRODUCT TECHNICAL DATA

- Medium thickness
- Color
- Max diameter aggregate
- Compression resistance at 28 days  
UNI EN 12930-3
- Fresh density
- Porosity
- Draining capacity (medium value)  
UNI EN 12697-40
- Free surface area (draining)
- Free surface area (draining)
- Material Yield
- Product appearance

10 cm pedestrian - 115 cm driveable (</=35 quintals) 20 cm driveable (> di 35 quintals)  
base color: natural gray, pigmentazione a ri-chiesta.  
from 6 to 11 mm – from 8 to 22  
 $> 15 \text{ Mpa N/mm}^2$   
 $> 1650 \text{ kg/m}^3$  about  
 $\geq 15\%$   
 $< 25\%$   
 $5.78 \cdot 10^{-3} \text{ m/s} \geq 150-180 \text{ liters/m}^2/\text{minute}$   
 $\geq 20\%$   
 $\geq 1 \text{ Mpa}$   
18 kg/m<sup>2</sup> spess. 1 cm\*\* about  
Bulk

\* Depending on the type and level of constipation achieved

\*\* Value for average constipation



Draining System



Frost Resistance



Non-slip



Eco-Friendly




High Resistance

## STRATIGRAPHIES



Prima Idro® permeable concrete - Pedestrian and cycle path  
\* Nominal values



Prima Idro® permeable concrete - Version for traffic.  
\* Nominal values

## BENEFITS



### COMPLETELY AND IMMEDIATELY DRAINING

The open-pored structure allows natural infiltration of rainwater into the subsoil. The minimum drainage rate of Prima Idro® is about 150-180 liters / m<sup>2</sup> / minute. The water table is regenerated.

### ENVIRONMENTAL BENEFITS

Prima Idro® helps reduce pollutants in runoff water. Water is retained by the top of the roadway, preventing it from being carried into waterways. The maximum flow rate through the sewer system is reduced.

### ECONOMIC BENEFITS

Prima Idro® is a valid alternative to the construction and subsequent maintenance of underground pipes for the collection, channeling and drainage of stormwater on paved surfaces, reducing the need for large cisterns by serving as a collection and retention area.

### HEAT ISLAND EFFECT

The surface cools faster because the porous material facilitates the passage of air.

### RESISTANCE AND SAFETY

Resistance to freeze-thaw cycles (snow-covered drainage concrete is able to eliminate it much faster than conventional flooring).

It significantly improves traffic safety during rain. High porosity allows faster melting of snow.

### DRIVABLE AND PEDESTRIAN

It has high mechanical strength and is suitable for both pedestrian and vehicular traffic.

### MAINTENANCE

Simple ordinary and extraordinary maintenance and lower operating costs.



IMPROVEMENT OF SURFACE QUALITY

## COLOR RANGE

Prima Idro® is available in natural grey or sample colors.



Natural Grey



Yellow



Brown



Red



Prima Idro®  
Secondary access road.



Prima Idro®  
Pedestrial path in residential area.



Prima Idro®  
Permeable concrete support, suitable for  
per draining natural gravel finishes like  
Prima Drain Stone®

## SOME OF OUR CUSTOMERS



CONTACT DETAILS  
**PAVIMENTI SPECIALI SRL**

**Milano - Sede operativa**

Via Piemonte, 23/B – 20098  
San Giuliano Milanese (MI)  
T +39 02.98282914

**Torino - Uffici amministrativi**

Via Vittorio Amedeo II, 19  
10121 Torino  
T +39 011.0714790

[info@primapavimenti.it](mailto:info@primapavimenti.it)  
[www.primapavimenti.it](http://www.primapavimenti.it)

**Switzerland**

Pavimenti Speciali Srl - Talenture S.A.  
Riva Albertolli 1  
6900 Lugano - Switzerland



OS 6 Classe IV  
OS 26 Classe IV  
OG 1 Classe III  
OG 3 Classe II